

THE 50dB RIVINGTON

Industry leading acoustic protection

KEY FEATURES



FIRE RATING
Up to 120 Minutes



ACOUSTIC
Up to 50dB



MAX DIMENSIONS
2780mm x 2574 mm



Boothindustries



Constructionline
Platinum Member

Combining advanced acoustic engineering with robust steel construction for demanding applications.

DOOR LEAF

111mm thick steel door leaf incorporating a dense acoustic core and reinforced internal construction for demanding environments. Approx. 135 kg per leaf.

FRAME

Heavy-duty steel frame assembly engineered to support large-format acoustic doorsets and maintain long-term structural integrity.

CONFIGURATION

Available in single and double-leaf arrangements with tested sizes up to 4500mm x 4500mm.

OPERATIONS

- Passive and active leaf configurations
- Vision panel option available
- Access control compatibility available

LOCKING SYSTEM

Multi-point Slimline locking with tower bolts, available with GSS3/4R or P5 Guard hardware.

SEALS & THRESHOLDS

Acoustic sealing system designed to maintain sound attenuation performance across the doorset assembly.

SURFACE FINISH

- Polyester powder-coated (PPC)
- Wet paint finish available
- Stainless steel finish

INSTALLATION

Suitable for concrete, brickwork and steelwork structures using Fischer FAZ II 10-30 A4 anchor fixings.



	Fire Rating	Acoustic	Security	U-Value	Smoke	Wind
50dB	E120	50dB	-	-	-	-