

THE

50dB RIVINGTON

Industry leading acoustic protection

KEY FEATURES



FIRE RATING
Up to 240 Minutes



ACOUSTIC
Up to 50dB



MAX DIMENSIONS
2780mm x 2574 mm



Boothindustries



Constructionline
Platinum Member

Combining advanced acoustic engineering with robust steel construction for demanding applications.

DOOR LEAF

111mm thick steel door leaf incorporating a dense acoustic core and reinforced internal construction for demanding environments. Approx. 135 kg per leaf.

FRAME

Heavy duty steel frame assembly engineered to support large format acoustic doorsets and maintain long term structural integrity.

CONFIGURATION

Available in single and double leaf arrangements with tested sizes up to 4500mm x 4500mm.

OPERATIONS

- Passive and active leaf configurations
- Vision panel option available
- Access control compatibility available

LOCKING SYSTEM

Multi point Slimline locking with tower bolts, available with GSS3/4R or P5 Guard hardware.

SEALS & THRESHOLDS

Acoustic sealing system designed to maintain sound attenuation performance across the doorset assembly.

SURFACE FINISH

- Polyester powder coated (PPC)
- Wet paint finish available
- Stainless steel finish

INSTALLATION

Suitable for concrete, brickwork and steelwork structures using Fischer FAZ II 10-30 A4 anchor fixings.



	Fire Rating	Acoustic*	Security	U-Value	Smoke	Wind
50dB	E240	50dB	–	–	–	–

**Push direction only*