

THE ASHFORD

Trusted protection where security matters most

KEY FEATURES



SECURITY
NPSA



MAX DIMENSIONS
2100mm x 1000mm



Boothindustries



Constructionline
Platinum Member

Designed for secure access applications, combining reinforced attack resistance with dependable protection in high security environments.

DOOR LEAF

58mm thick door leaf with laminated timber core encapsulated in galvanised steel skins, designed to withstand hinge side attack. Approximately 150kg.

FRAME

Four sided pressed steel frame with fully welded corners in Zintec finish.

SURFACE FINISH

- Single or double leaf options
- Inward or outward opening
- Left hand or right hand options

OPERATION

Designed for manual operation with inward or outward opening functionality depending on project requirements.

LOCKING SYSTEM

Rim lock system compatible with Medway spin dial, Fraser bar emergency exit device, or Avon key locks. Approved with ILS scroll lock securing a 3 point Solent system with emergency egress.

IRONMONGERY

- Three butt hinges with high integrity hinge bolts
- Lever handles fitted to both sides
- Compatible with a range of locking devices and emergency exit hardware
- Additional ironmongery options available on request

SEALS & THRESHOLD

5mm low plate threshold with sealing arrangements available on request. Vision panels not available.

SURFACE FINISH

- Polyester powder coated (PPC)
- Wet paint finish available

INSTALLATION

Installation requires 10mm head clearance and 5mm jamb clearance. Suitable for installation into concrete or brickwork structures.



	Fire Rating	Acoustic	Security	U-Value	Smoke	Wind
Ashford	–	–	NPSA	–	–	–