

THE BUTETOWN

Designed specifically for road tunnel safety

KEY FEATURES



FIRE RATING
Up to 120 minutes



MAX DIMENSIONS
1956mm x 2156mm



Boothindustries



Constructionline
Platinum Member

Designed for high traffic environments, combining durable stainless steel construction with reliable double egress operation for safe, efficient movement and emergency escape access.

DOOR LEAF

70mm stainless steel leaf with pressed skins, welded construction, and an insulated core for durability in demanding environments.

FRAME

215mm x 50mm "P" shaped 316L single rebate frame profile manufactured from 6mm pressed stainless steel, designed for double egress and high traffic infrastructure applications.

OPERATION

Smooth and reliable double egress operation designed to support efficient movement and emergency escape routes.

LOCKING SYSTEM

Surelock Slimline 2017 SL204-05 stainless steel push bar fitted as standard.

IRONMONGERY

Pyroplex Graphite intumescent seals fitted to support fire protection performance. Push bar escape hardware assists safe and efficient exit.

SEALS & THRESHOLDS

- Pyroplex graphite intumescent seals fitted as standard
- 6mm x 214mm flat threshold detail with tapered option available for Part M compliance.
- Polished stainless steel available

SURFACE FINISH

- Polyester powder coated (PPC)
- Wet paint finish available
- Polished stainless steel available

INSTALLATION

Suitable for installation into brickwork, blockwork, concrete and steelwork using Fischer FAZ II 12/30 A4 fixings.



	Fire Rating	Acoustic	Security	U-Value	Smoke	Wind
Butetown	E240	–	–	–	–	–